




**TYPICAL SECTION**

No Scale

**NOTES:**

1. This roadway section to be applied to roadways with the following characteristics:
  - a. At locations where development exists.
  - b. A 10-year future A.D.T. projection is less than 400.
  - c. Required cuts and fills are greater than 2.4 m (8') when a 7.3 m (24') curb to curb width is used.
2. Provide slope easements if required.
3. Roadway may be center crowned if curb and gutter installed in lieu of A.C. dike.
4. Standard does not provide for on street parking.
5. For additional information see "Third Report on Blackberry Hill Road Area Roadways" dated Jan. 6, 1978 as approved by the Board of Supervisors on Jan. 16, 1978.
6. Provide erosion control per County Land Development Regulations.
7. Turnouts will be required every 90 m (300').

METRIC (& ENGLISH) UNITS

		<b>SANTA CLARA COUNTY ROADS AND AIRPORTS DEPARTMENT</b>			<b>STANDARD DETAILS HILLSIDE ROADS TYPICAL SECTION</b>	DRAWING NO. <b>A</b>		
		DESIGNED: VAP 09/04/97 DATE: LRE 09/04/97 DRAWN: VAP/TH 9/12/97 CHECKED:	SUBMITTED: WORK ORDER: LEVEL BOOK: TRANSIT BOOK:	APPROVAL: 		<b>8</b>		
NO.	REVISIONS	BY	DATE	APP'D	PROJECT NO.	CONTRACT NO.	FILE NO.	SHIT NO. 2 of 2