



<u>RIGHT</u>



BOTH

130mm (5") (TYP.) 16mm (5/8") R=19mm (3/4") 5mm (3/16") — 25mm (1") 102mm (4") 25mm (1") 16mm (5/8") 13mm (1/2") 6mm (1/4") 16mm (5/8") 16mm (5/8")




ALTERNATE ARROW DIRECTIONS



SIGN DIMENSIONS



- 1) SIGN SHALL HAVE PORCELAIN ENAMEL FINISH.
- 2) CONTROL BUTTON SHALL BE RAISED AND HAVE A 50mm (2") MINIMUM DIAMETER.
- 3) THE FORCE REQUIRED TO OPERATE THE CONTROL SHALL BE LIMITED TO 22.2 N (5 LBF).
- 4) STAINLESS STEEL PHILIPS HEAD SCREWS SHALL BE USED FOR SIGN AND PUSHBUTTON MOUNTING TO HOUSING.






MODIFIED TYPE B PUSHBUTTON

METRIC (& ENGLISH) UNITS

SANTA CLARA COUNTY ROADS AND AIRPORTS DEPARTMENT 04/15/97 DESIGNED STQ 04/15/97

DRAWN D4/15/97

CHECKED 04/15/97







STANDARD DETAILS
PEDESTRIAN PUSHBUTTON ASSEMBLY